

AFFORDABLE AND VERSATILE

JUICI ID 3 - 7" TOUCH- smart design - easy refill - automatic cleaning!
Perfect for small hotels, buffets, offices and kiosks.

- Space for 3 x 5 liter Bag-in-Box (WxHxD:350x200x300 mm) in the device
- 3 drinks + chilled water
- Slim design for plenty of counter space (WxHxD:400x590x470mm)
- Preselection CO₂ or HOT-OPTIONAL
- Central drink exit with LED-lighting (hygienic tempered glass tube)
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control for dosage and quantity
- Reliable and durable-premium quality materials
- Robust surfaces, stainless steel and metal
- Easy handling- fast refill
- Perfect mixing result due to patented MidMix® -technology
- Flexible programming to fulfill customer requirements
- 7" TOUCH-DISPLAY for flexible design and presentation of drink selections and functions
- Maintenance-free dry cooling unit, high capacity
- High-quality decorative panel of your choice (OPTIONAL)



Polar Oak
(bright wood)



Barrique Oak
(medium bright wood)



Zorro
(dark wood)



Moonwalk
(bright stone)



Black Matt
(black core)

Available in the following versions:

JUICI ID 3 STILL, JUICI ID 3 CO₂, JUICI ID 3 Hot & Cold

ASCO Drink Machines GmbH
 Steyrer Straße 80, A - 4470 Enns,
 office@asco.at -
 www.asco.at
 +43 / (0)7223 / 86197-0

TECHNICAL DATA

DATA	JUICI ID 3 STILL	JUICI ID 3 CO ₂	JUICI ID 3 Hot & Cold
Art. Nr.	frucB0331JI	frucB0332JI	frucB0333JI
Width in mm	400 mm	400 mm	400 mm
Height in mm	590 mm	590 mm	590 mm
Depth in mm	470 mm	470 mm	470 mm
Exit height	160 - 240 mm	160 - 240 mm	160 - 240 mm
Weight	34 kg	38 kg	36 kg
Preselections	3 - 9	6 - 12	6 - 12
Product selection screen (incl. water)	3 - 6	6 - 12	6 - 12
aut. caraffe preselection (extra)	OPTIONAL	OPTIONAL	OPTIONAL
ESI Productscreen ²	✓	✓	✓
Flavours	3	3	3
Mixing ratio concentrate	1+4 ...1+49	1+4 ...1+49	1+4 ...1+49
Bag-space dimensionen WxHxD	350x200x300 mm	350x200x300 mm	350x200x300 mm
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Cooling capacity	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 - max 6	min 1,5 - max 6	min 1,5 - max 6
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	250 W	320 W	2.600 W
with CO ₂ -Carbonator	-	✓	-
FSS ¹	✓	✓	✓
Flowmeter (water)	✓	✓	✓
Dispensing area LED light	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	-	-	-
Payment system	-	-	-
Monitoring sanitation/ cleaning interval	✓	✓	✓
Syrup Injection Valve (SIV ³)	✓	✓	✓
Automatic cup sensor	OPTIONAL	OPTIONAL	OPTIONAL
Water gallon + pumpset	OPTIONAL	OPTIONAL	OPTIONAL

All our models are equipped with the unique and patented mixing system MidMix III.

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV - syrup injection valve for perfect mixing result

*Installation of water reduction necessary

SIZE INCL. PACKAGING	JDM ID 3 STILL	JDM ID 3 CO ₂	JDM ID 3 Hot & Cold
Width	570 mm	570 mm	570 mm
Height	700 mm	700 mm	700 mm
Depth	470 mm	470 mm	470 mm
Weight incl. Packaging	36 kg	40 kg	38 kg
MACHINE PACKAGE/PALLET			
Europallet 80 x 120 cm	4	4	4
UK-size Palette 100 x 120 cm	8	8	8

