

# SPATIAL WONDER, ELEGANT AND TIMELESS!

THE JDM CT – OUR BEAUTIFULLY SHAPED MODEL,  
THAT SAVES YOU VALUABLE COUNTER SPACE.

- 4/6 drink selection buttons + chilled water
- Bag-in-Box concentrates are stored in existing furniture/base cabinets (for use of large bags e.g. 10 litre)
- Preselection Hot or CO<sub>2</sub> – OPTIONAL (model Hot & Cold or CO<sub>2</sub>)
- 1 central drink exit with LED lighting (hygienic tempered glass tube)
- Adjustable dispensing height
- Automatic cleaning and increased hygiene through airtight seal of concentrates
- Fully electronic control of concentrate dosage and output quantities
- Reliable and durable – premium materials, robust surfaces
- Ease of use – easy refilling, programming, service and cleaning
- Perfect mixing result through patented MidMix®-system
- Multilingual LCD-Info Display
- Preparation for payment systems + accounting
- Carafe switch for quick serving by service staff
- Design of the drink dispense tower – OPTIONAL
- Base cabinet - OPTIONAL

## Available in the following versions:

JDM CT L-4/6 STILL, JDM CT L-4/6 CO<sub>2</sub>,  
JDM CT L 4/6 Hot & Cold



adjustable  
dispensing  
height for  
JDM CT L



ESI (Easy  
slide in)  
labels



Table or wall  
installation possible

DATA	JDM CT L-4 STILL	JDM CT L-4 CO2	CT L-4 Hot & Cold	JDM CT L-6 STILL	JDM CT L-6 CO2	CT L-6 Hot & Cold
Price in € excl. VAT	€	€	€	€	€	€
Art. Nr.	frucB0501	frucB0506	frucB0503	frucB0511	frucB0516	frucB0513
Control-/Dispensing unit with tower	L 4	L 4	L 4	L 6	L 6	L 6
Width	210 mm	210 mm	210 mm	210 mm	210 mm	210 mm
Height	545 mm	545 mm	545 mm	545 mm	545 mm	545 mm
Depth	200 mm	200 mm	200 mm	200 mm	200 mm	200 mm
Exit height	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm	140 - 310 mm
Weight	6 kg	6 kg	6 kg	6 kg	6 kg	6 kg
Preselections	1	1	1	1	1	1
Product selection buttons (incl. water)	5	5	5	7	7	7
Automatic carafe preselection (Extra)	✓	✓	✓	✓	✓	✓
ESI product labels <sup>2</sup>	✓	✓	✓	✓	✓	✓
Flavours	4	4	4	6	6	6
Mixing ratio concentrates	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49	1+4 bis 1+49
Concentrates in machine	-	-	-	-	-	-
Dosage of product selection	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS	150-500ml / PULS
Dosage of preselection EXTRA/jug	max 2000ml	max 2000ml	max 2000ml	max 2000ml	max 2000ml	max 2000ml
Technics box	-	-	-	-	-	-
Width	260 mm	260 mm	260 mm	260 mm	260 mm	260 mm
Height	360 mm	360 mm	360 mm	360 mm	360 mm	360 mm
Depth	460 mm	460 mm	460 mm	460 mm	460 mm	460 mm
Weight	max. 23 kg	max. 27 kg	max. 25 kg	max. 24 kg	max. 28 kg	max. 26 kg
Distance technics box/ dispensing unit vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance technics box/ dispensing unit horizontal	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Distance concentrate/ technics box vertical	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m	max. 1,5 m
Distance concentrate/ technics box horizontal	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m	max. 5,0 m
Cooling capacity	28 l/h	28 l/h	28 l/h	28 l/h	28 l/h	28 l/h
Dispensing temperature	5°C - ambient	5°C - ambient	5°C - 75°C	5°C - ambient	5°C - ambient	5°C - 75°C
Water pressure in bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar	min 1,5 bar/max 6 bar
Voltage	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz	230 V/ 50 Hz
Power max.	250 W	250 W	2600 W	250 W	250 W	2600 W
with CO2-carbonator	-	✓	-	-	✓	-
FSS <sup>1</sup>	✓	✓	✓	✓	✓	✓
Flowmeter (water)	✓	✓	✓	✓	✓	✓
Dispense tower glass LED backlight	OPTIONAL	-	OPTIONAL	OPTIONAL	-	OPTIONAL
Dispensing area LED light	✓	✓	✓	✓	✓	✓
Coin validator/cashless	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Bookkeeping	✓	✓	✓	✓	✓	✓
Payment systems	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE	parallel / EXE
Syrup Injection Valve (SIV <sup>3</sup> )	✓	✓	✓	✓	✓	✓
Water gallon + pumpset	OPTIONAL	OPTIONAL	-	OPTIONAL	OPTIONAL	-
Control of Disinfection and Sanitation intervals	✓	✓	✓	✓	✓	✓

**ALL our models are equipped with the unique and patented mixing system MidMix II.**

- 1) FSS = Flood security system: avoids water flood problems due to extra safety valve on water entrance.
- 2) ESI = easy slide in: for fast and easy change of product labels
- 3) SIV - syrup injection valve for perfect mixing result

SIZE INCL. PACKAGING	JDM CT L-4 STILL	JDM CT L-4 CO2	CT L-4 Hot & Cold	JDM CT L-6 STILL	JDM CT L-6 CO2	CT L-6 Hot & Cold
Width	570 mm	570 mm	570 mm	570 mm	570 mm	570 mm
Height	670 mm	670 mm	670 mm	670 mm	670 mm	670 mm
Depth	310 mm	310 mm	310 mm	310 mm	310 mm	310 mm
Weight incl. Packaging	32 kg	36 kg	34 kg	33 kg	37 kg	35 kg
<b>MACHINE PACKAGE/PALLET</b>						
Europallet 80 x 120 cm	8	8	8	8	8	8
UK-size pallet 100 x 120 cm	12	12	12	12	12	12

